MÉTRO - Shower column

E26588

Collection: MÉTRO

Finish*:

CP - Chrome

BL - Matte Black

Main features:

Features

- **DIMENSIONS:** 33.40 x 54.60 x 131.50 cm
- **MATERIAL:** Metal
- **FLOW RATE:** 10 l/mn
- **TYPE:** Single-lever
- **WITH OR WITHOUT BRASSWARE:** WITH FITTINGS
- **SHOWER TAPS-DIVERTER:** Integrated
- **SHOWER TAPS-MAXIMUM TEMPERATURE:** 50°C
- **HOSE TYPE:** Smooth, anti-twist, metal look
- **WEIGHT:** 5.6 kg
- **INSTALLATION TYPE:** Wall-mount
- **CONNECTION:** With wall connectors
- **SHOWER TAPS-WATER/ENERGY SAVING:** Water-saving
- **SINGLE-LEVER TAPS:** Thermostatic
- **SHOWER TAPS-SAFETY STOP:** 38°C
- **SHOWER TAPS-HANDSHOWER FLOW:** 10 L/min
- **NUMBER OF SPRAYS:** 3

Consumer benefits

• MINIMALIST LINES: Delicate design that blends harmoniously with all bathroom styles and combines with all the ranges.

• COMFORT: Thermostatic cartridge with ultra-rapid regulation that ensures a constant water temperature, precise adjustment and rapid arrival at selected temperature. Stop indicates comfort temperature (37°C).

• ANTI-TWIST SYSTEM: Smooth, anti-twist shower hose.

• PRACTICAL: Ergonomic handles with built-in diverter.

• ULTRA-THIN METAL SHOWERHEAD: Wide diameter Ø 300 for very comfortable water coverage under the shower.

• HIGH-QUALITY WARRANTY: Polished chrome finish - 10 years. Mechanisms - 5 years. Metal handles and shower head.

• NO-SCALD SAFETY: Hot water compartment in the rear. Maximum temperature 50°C. Flow stops in case of cold water shutoff.

Installation benefits

• EASY INSTALLATION: Arm can be adjusted and swivelled during installaiton.

• WATER HEATER COMPTABILITY: Compatible with any hot water heater of at least 18kW.

Optional products

- E24316: Anti-slip shelf

Product Specification: Shower column. E26588. Collection: MÉTRO. DIMENSIONS: 33.40 x 54.60 x 131.50 cm. WEIGHT: 5.6 kg. MATERIAL: Metal. INSTALLATION TYPE: Wall-mount. FLOW RATE: 10 l/mn. CONNECTION: With wall connectors. TYPE: Single-lever. SHOWER TAPS-WATER/ENERGY SAVING: Water-saving. WITH OR WITHOUT BRASSWARE: WITH FITTINGS. SINGLE-LEVER TAPS: Thermostatic. SHOWER TAPS-DIVERTER: Integrated. SHOWER TAPS-SAFETY STOP: 38°C. SHOWER TAPS-MAXIMUM TEMPERATURE: 50°C. SHOWER TAPS-HANDSHOWER FLOW: 10 L/min. HOSE TYPE: Smooth, anti-twist, metal look. NUMBER OF SPRAYS: 3.

This document is not contractual

Due to possible variations in computer and printer calibrations, technical factors and certain finish characteristics, the colors you see may not accurately portray the actual colors and are provided as a guide only.

Technical drawing

Product Specification: Shower column. E26588. Collection: MÉTRO. DIMENSIONS: 33.40 x 54.60 x 131.50 cm. WEIGHT: 5.6 kg. MATERIAL: Metal. INSTALLATION TYPE: Wall-mount. FLOW RATE: 10 l/mn. CONNECTION: With wall connectors. TYPE: Single-lever. SHOWER TAPS-WATER/ENERGY SAVING: Water-saving. WITH OR WITHOUT BRASSWARE: WITH FITTINGS. SINGLE-LEVER TAPS: Thermostatic. SHOWER TAPS-DIVERTER: Integrated. SHOWER TAPS-SAFETY STOP: 38°C. SHOWER TAPS-MAXIMUM TEMPERATURE: 50°C. SHOWER TAPS-HANDSHOWER FLOW: 10 L/min. HOSE TYPE: Smooth, anti-twist, metal look. NUMBER OF SPRAYS: 3.

This document is not contractual

**Due to possible variations in computer and printer calibrations, technical factors and certain finish characteristics, the colors you see may not accurately portray the actual colors and are provided as a guide only.*